


## WiFi 6 Dual Band Wall Mount AP NX-AP3000-4PW6



### OVERVIEW

NX-AP3000-4PW6 is a high-performance, high-speed indoor 11ax wall-mounted panel AP with 2.4G and 5.8GHz dual-band wireless services, providing a cleaner wireless environment and more stable wireless access.

### FEATURES

- › WiFi 6 802.11 b/g/n/ax
- › Simultaneously running 2.4GHz (574Mbps) and 5GHz (2400Mbps) to achieve maximum wireless throughput.
- › Support hardware watchdog function, automatic recovery of abnormal devices, maintenance free.
- › The heat sink is treated with a special surface coating, resulting in a more ideal heat dissipation effect.
- › Supports 48V PoE.




### HARDWARE SPECIFICATIONS

SPECIFICATIONS	NX-AP3000-4PW6
Flash	SPI NOR 16MB
DDR3L	256M
2.4G Frequency	2.4GHz~2.484GHz
2.4G Protocol	802.11 b/g/n/ax
5G Frequency	5.150GHz~5.850GHz
5G Protocol	802.11 a/n/ac/ax
2.4G Antenna	2*1.7dBi
5G Antenna	2*2.9dBi



## WiFi 6 Dual Band Wall Mount AP NX-AP3000-4PW6




### HARDWARE SPECIFICATIONS

SPECIFICATIONS	NX-AP3000-4PW6				
Data Rate	5G: 2400Mbps 2.4G: 574Mbps				
2.4G TX Power	802.11b	11M	18±2dBm	1M	20±2dBm
	802.11g	54M	16±2dBm	6M	18±2dBm
	802.11n HT20	MCS7	15±2dBm	MCS0	17±2dBm
	802.11n HT40	MCS7	15±2dBm	MCS0	17±2dBm
	802.11ax HT20	MCS11	13±2dBm	MCS0	15±2dBm
	802.11ax HT40	MCS11	13±2dBm	MCS0	15±2dBm
5G TX Power	802.11a	54M	15±2dBm	6M	17±2dBm
	802.11n HT20	MCS7	14±2dBm	MCS0	16±2dBm
	802.11n HT40	MCS7	14±2dBm	MCS0	16±2dBm
	802.11ac HT20	MCS7	13±2dBm	MCS0	15±2dBm
	802.11ac HT40	MCS7	13±2dBm	MCS0	15±2dBm
	802.11ac HT80	MCS9	13±2dBm	MCS0	15±2dBm
	802.11ax HT20	MCS11	12±2dBm	MCS0	14±2dBm
	802.11ax HT40	MCS11	12±2dBm	MCS0	14±2dBm
	802.11ax HT80	MCS11	12±2dBm	MCS0	14±2dBm
802.11ax HT160	MCS11	12±2dBm	MCS0	14±2dBm	
2.4G Receiving Sensitivity	802.11b	11M	-83dBm	1M	-90dBm
	802.11g	54M	-70dBm	6M	-84dBm
	802.11n HT20	MCS7	-68dBm	MCS0	-83dBm
	802.11n HT40	MCS7	-66dBm	MCS0	-83dBm
	802.11ax HT20	MCS11	-56dBm	MCS0	-83dBm
	802.11ax HT40	MCS11	-53dBm	MCS0	-83dBm
5G Receiving Sensitivity	802.11a	54M	-70dBm	6M	-83dBm
	802.11n HT20	MCS7	-67dBm	MCS0	-83dBm
	802.11n HT40	MCS7	-64dBm	MCS0	-83dBm
	802.11ac HT20	MCS7	-58dBm	MCS0	-83dBm
	802.11ac HT40	MCS7	-57dBm	MCS0	-83dBm
	802.11ac HT80	MCS9	-56dBm	MCS0	-85dBm
	802.11ax HT20	MCS11	-57dBm	MCS0	-83dBm
	802.11ax HT40	MCS11	-56dBm	MCS0	-83dBm
	802.11ax HT80	MCS11	-53dBm	MCS0	-82dBm
802.11ax HT160	MCS11	-51dBm	MCS0	-88dBm	



## WiFi 6 Dual Band Wall Mount AP NX-AP3000-4PW6



### HARDWARE SPECIFICATIONS

SPECIFICATIONS	NX-AP3000-4PW6
2.4G EVM	802.11b:≤-10 dB ; 802.11g:≤-25 dB ; 802.11n:≤-28dB ; 802.11ax: ≤-35 dB
5G EVM	802.11a:≤-25 dB ; 802.11n:≤-28 dB ; 802.11ac:≤-32 dB ; 802.11ax:≤-35 dB
PPM	±20ppm
WAN	1*10/100/1000M WAN, support 48V POE
LAN	1*10/100/1000M LAN
POE	802.3af
Reset	Reset to factory settings by pressing 6-10 seconds
Indicators	SYS
Max Power Consumption	12W
ESD	Air:±8K, Touch:±4K
Electrical Surge	Common Mode: 1K, Differential Mode: 0.5K
Size	86mm*86mm*42.8mm
Weight	0.26kg
Temperature	Working: -10°C to 40°C ; Storage: -40°C to 70°C ; Humidity: 5%~95%(Non-Condensing)

#### USA

Tel +1 877 677 4040  
info@nodexon.com  
152 East 118th Street,  
New York, NY 10035

#### EUROPE

Tel +44 746 6717286  
uk@nodexon.com  
Fairbourne Drive, Atterbury,  
Buckinghamshire, UK

#### MIDDLE EAST

Tel +971 44 558570  
mena@nodexon.com  
Boulevard Plaza Tower One, Level 3,  
Downtown Dubai, UAE

